

Lightwave Logic, Inc.  
Form 10-K  
March 31, 2014

---

---

UNITED STATES  
SECURITIES AND EXCHANGE COMMISSION  
Washington, D.C. 20549

FORM 10-K

þ ANNUAL REPORT PURSUANT TO SECTION 13 OR 15(d) OF THE  
SECURITIES EXCHANGE ACT OF 1934

For the fiscal year ended December 31, 2013

.. TRANSITION REPORT PURSUANT TO SECTION 13 OR 15 (D) OF THE  
SECURITIES EXCHANGE ACT OF 1934

For the transition period from \_\_\_\_\_ to \_\_\_\_\_

Commission file number: 0-52567

Lightwave Logic, Inc.  
(Exact name of registrant as specified in its charter)

Nevada  
(State or other jurisdiction of  
incorporation or organization)

82-049-7368  
(I.R.S. Employer  
Identification No.)

1831 Lefthand Circle, Suite C, Longmont, CO  
(Address of principal executive offices)

80501  
(Zip Code)

(Registrant's Telephone Number, including Area Code): 720-340-4949

Securities registered pursuant to Section 12(b) of the Act

Title of each class registered	Name of each exchange on which registered
--------------------------------	--

Securities registered pursuant to section 12(g) of the Act:

Common Stock, Par Value \$0.001  
(Title of class)

Indicate by check mark if the Registrant is a well-known seasoned issuer, as defined in Rule 405 of the Securities Act. Yes  No

Edgar Filing: Lightwave Logic, Inc. - Form 10-K

Indicate by check mark if the Registrant is not required to file reports pursuant to Section 13 or 15(d) of the Act. Yes  No

Indicate by check mark whether the registrant (1) has filed all reports required to be filed by Section 13 or 15(d) of the Securities Exchange Act of 1934 during the preceding 12 months (or for such shorter period that the registrant was required to file such reports), and (2) has been subject to such filing requirements for the past 90 days. Yes  No

Indicate by check mark whether the registrant has submitted electronically and posted on its corporate Website, if any, every Interactive Data File required to be submitted and posted pursuant to Rule 405 of Regulation S-T (§232.405 of this chapter) during the preceding 12 months (or for such shorter period that the registrant was required to submit and post such files). Yes  No

Indicate by check mark if disclosure of delinquent filers pursuant to Item 405 of Regulation S-K is not contained herein, and will not be contained, to the best of the registrant's knowledge, in definitive proxy or information statements incorporated by reference in Part III of this Form 10-K or any amendment to this Form 10-K.

Indicate by check mark whether the registrant is a large accelerated filer, an accelerated filer, a non-accelerated filer or a smaller reporting company. See definitions of "large accelerated filer," "accelerated filer" and "smaller reporting company" in Rule 12b-2 of the Exchange Act. (Check one):

Large Accelerated <input type="checkbox"/>	Accelerated Filer <input type="checkbox"/>
Filer	
Non-Accelerated <input type="checkbox"/>	Smaller reporting <input checked="" type="checkbox"/>
filer	company

Indicate by check mark whether the registrant is a shell company (as defined in Rule 12b-2 of the Exchange Act of 1934). Yes  No

The aggregate market value of the voting and non-voting common equity held by non-affiliates of the registrant was approximately \$38,193,179 as of June 30, 2013.

As of March 31, 2014, there were 53,080,469 shares outstanding of the registrant's common stock, \$.001 par value.

---

---

## Table of Contents

	Page
<b>PART I</b>	
Item 1. Business	1
Item 1A. Risk Factors	19
Item 1B. Unsolved Staff Comments	33
Item 2. Properties	33
Item 3. Legal Proceedings	33
Item 4. Mine Safety Disclosures	33
<b>PART II</b>	
Item 5. Market for Registrant's Common Equity, Related Stockholder Matters and Issuer Purchases of Equity Securities	34
Item 6. Selected Financial Data	36
Item 7. Management's Discussion and Analysis of Financial Condition and Results of Operations	36
Item 7A. Quantitative and Qualitative Disclosures About Market Risk	45
Item 8. Financial Statements and Supplementary Data	45
Item 9. Changes in and Disagreements with Accountants on Accounting and Financial Disclosure	45
Item 9A. Controls and Procedures	45
Item 9B. Other Information	46
<b>PART III</b>	
Item 10. Directors, Executive Officers and Corporate Governance	47
Item 11. Executive Compensation	50
Item 12. Security Ownership of Certain Beneficial Owners and Management and Related Stockholder Matters	53
Item 13. Certain Relationships and Related Transactions, and Director Independence	55
Item 14. Principal Accounting Fees and Services	56
<b>PART IV</b>	
Item 15. Exhibits, Financial Statement Schedules	57

Forward-Looking Statements

This report on Form 10-K contains forward-looking statements. Forward-looking statements involve risks and uncertainties, such as statements about our plans, objectives, expectations, assumptions or future events. In some cases, you can identify forward-looking statements by terminology such as “anticipate,” “estimate,” “plan,” “project,” “continuing,” “ongoing,” “expect,” “we believe,” “we intend,” “may,” “should,” “will,” “could” and similar expressions denoting uncertainty or an action that may, will or is expected to occur in the future. These statements involve estimates, assumptions, known and unknown risks, uncertainties and other factors that could cause actual results to differ materially from any future results, performances or achievements expressed or implied by the forward-looking statements. You should not place undue reliance on these forward-looking statements.

Factors that that are known to us that could cause a different result than projected by the forward-looking statement, include, but are not limited to:

- lack of available funding
- general economic and business conditions
- competition from third parties
- intellectual property rights of third parties
- regulatory constraints
- changes in technology and methods of marketing
- delays in completing various engineering and manufacturing programs
- changes in customer order patterns
- changes in product mix
- success in technological advances and delivering technological innovations
- shortages in components
- production delays due to performance quality issues with outsourced components
- those events and factors described by us in Item 1.A “Risk Factors”
- other risks to which our Company is subject
- other factors beyond the Company's control.

Any forward-looking statement made by us in this report on Form 10-K is based only on information currently available to us and speaks only as of the date on which it is made. We undertake no obligation to publicly update any forward-looking statement, whether written or oral, that may be made from time to time, whether as a result of new information, future developments or otherwise.

PART I

Item 1. Business.

Our Business Development

PSI-TEC Corporation (“PSI-TEC”) was founded in 1991 and incorporated under the laws of the State of Delaware on September 12, 1995. Dr. Frederick J. Goetz founded PSI-TEC in Upland, Pennsylvania where he established a laboratory with a small amount of private funding. PSI-TEC subsequently moved its operations to laboratory space provided by the U.S. Army on the Aberdeen Proving Grounds in cooperation with a division of the Department of Defense for the advancement of ultra wide-bandwidth satellite telecommunications. Thereafter, PSI-TEC commenced operations of its own organic synthesis and thin-films laboratory in Wilmington, Delaware.

In order to become a non-reporting publicly-traded corporation, in July 2004 PSI-TEC reorganized with Eastern Idaho Internet Services, Inc. (“Eastern Idaho”) whereby (i) Eastern Idaho changed its name to PSI-TEC Holdings, Inc. (“PSI-TEC Holdings”); (ii) PSI-TEC Holdings acquired all of the issued and outstanding shares of PSI-TEC stock; (iii) PSI-TEC became PSI-TEC Holdings’ wholly-owned operating subsidiary; and (iv) PSI-TEC Holdings’ then sole officer and director resigned, PSI-TEC’s nominees were elected to PSI-TEC Holdings’ board of directors and new management was appointed. For accounting purposes, this acquisition transaction was accounted for as a reverse-acquisition, whereby PSI-TEC was deemed to have purchased PSI-TEC Holdings. As a result, the historical financial statements of PSI-TEC became the historical financial statements of PSI-TEC Holdings.

Immediately prior to the time of the reorganization transaction, Eastern Idaho was a non-reporting development stage company whose stock was traded on the OTC: Pink Sheets. It had no substantive business operations and it was seeking other business opportunities. Eastern Idaho was originally incorporated under the laws of the State of Nevada on June 24, 1997 to operate as an Internet services marketing firm. It was unsuccessful in this venture, and in June 1998 it ceased its operations and sold all of its operating assets.

On October 20, 2006, in order to consolidate the operations of PSI-TEC Holdings, Inc. and PSI-TEC Corp. (PSI-TEC Holdings, Inc.’s wholly owned subsidiary), PSI-TEC Holdings, Inc. and PSI-TEC Corp. merged; and PSI-TEC Holdings, Inc., a Nevada corporation, became the surviving entity and subsequently changed its name to Third-Order Nanotechnologies, Inc. No change of control or domicile occurred as a result of the merger.

On March 10, 2008, Third-order Nanotechnologies, Inc. changed its name to Lightwave Logic, Inc. to better suit its strategic business plan and to facilitate stockholder recognition of the Company and its business.

Unless the context otherwise requires, all references to the “Company,” “we,” “our” or “us” and other similar terms means Lightwave Logic, Inc., a Nevada corporation.

Our principal executive office is located at 1831 Lefthand Circle, Suite C, Longmont, CO 80501, and our telephone number is (720) 340-4949. Our website address is [www.lightwavelogic.com](http://www.lightwavelogic.com). No information found on our website is part of this report. Also, this report includes the names of various government agencies and the trade names of other companies. Unless specifically stated otherwise, the use or display by us of such other parties’ names and trade names in this report is not intended to and does not imply a relationship with, or endorsement or sponsorship of us by, any of these other parties.



## Overview

We are a development stage, electro-optical device and organic nonlinear materials company. Our primary area of expertise is the chemical synthesis of chromophore dyes used in the development of organic Application Specific Electro-Optic Polymers (ASEOP) and Organic Non-Linear All-Optical Polymers (NLAOP) that have high electro-optic and optical activity. Our family of materials are thermally and photo-chemically stable, which we believe could have utility across a broad range of applications in devices that address markets like, telecommunication, data communications, high-speed computing and photovoltaic cells. Secondly, the company is developing proprietary electro-optical and all-optical devices utilizing the advanced capabilities of our materials for the application in the fields mentioned above.

Electro-optic devices convert data from electric signals into optical signals for use in communications systems and in optical interconnects for high-speed data transfer. We expect our patented and patent-pending optical materials, when completed and tested, to be the core of the future generations of optical devices, modules, sub-systems and systems that we will develop or be licensed by electro-optic device manufacturers, such as telecommunications component and systems manufacturers, networking and switching suppliers, semiconductor companies, aerospace companies and government agencies.

Our optical polymers (polymers) are property-engineered at the molecular level (nanotechnology level) to meet the exacting thermal, environmental and performance specifications demanded by electro-optic devices. We believe that our patented and patent pending technologies will enable us to design optical polymers that are free from the numerous diverse and inherent flaws that plague competitive polymer technologies employed by other companies and research groups. We engineer our polymers with the intent to have temporal, thermal, chemical and photochemical stability within our patented and patent pending molecular architectures.

Our non-linear all optical polymers have demonstrated resonantly enhanced third-order properties approximately 2,630 times larger than fused silica, which means that they are highly photo-optically active in the absence of an RF layer. In this way they differ from other optical polymers and are considered more advanced next-generation materials.

Our patented and patent pending molecular architectures are based on a well-understood chemical and quantum mechanical occurrence known as aromaticity. Aromaticity provides a high degree of molecular stability. Aromaticity is what will enable our core molecular structures to maintain stability under a broad range of polymerization conditions that otherwise appear to affect other current polymer molecular designs. Polymers, polymer-based devices, hybrid devices and the processes used to create them are often patentable, which can provide the developers of such technology with a significant competitive advantage. We consider our proprietary intellectual property to be unique.

## Glossary of Select Technology Terms Used Herein

### All-optical devices

All-optical devices convert data in the form of input light signals to a secondary light data stream. The future market of all-optical devices and switches is expected to include all-optical transistors.

### All-optical transistors

All-optical transistors are devices currently under development that use an input light signal to switch a secondary light signal. All-optical transistors are expected to enable the fabrication of an entirely new generation of high-speed computers that operate on light instead of electricity. We believe that this will significantly improve computation speeds.





#### Aromaticity

Aromaticity causes an extremely high degree of molecular stability. It is a molecular arrangement wherein atoms combine into a ring or rings and share their electrons among each other. Aromatic compounds are extremely stable because the electronic charge distributes evenly over a great area preventing hostile moieties, such as oxygen and free radicals, from finding an opening to attack.

#### CLD-1

An electro-optic material based upon unstable polyene molecular architectures. Unlike our own molecular designs, CLD-1 is not a CSC model molecule and exhibits thermal degradation at low temperatures (~250 C) making it less suitable for commercial and military applications.

#### CSC (Cyclical Surface Conduction) theory

Most charge-transfer dyes (e.g. Disperse Red 1, CLD, FTC) are based upon a polyene architecture wherein the ground state and first excited state differ by the alteration of single and double bonds. CSC model molecules use nitrogenous heterocyclical structures.

#### Electro-optic devices

Electro-optic devices convert data from electric signals into optical signals for use in communications systems and in optical interconnects for high-speed data transfer.

#### Electro-optic material

Electro-optic material is the core active ingredient in high-speed fiber-optic telecommunication systems. Electro-optic materials are materials that are engineered at the molecular level. Molecular level engineering is commonly referred to as "nanotechnology."

#### Electro-optic modulators

Electro-optic modulators are electro-optic devices that perform electric-to-optic conversions within the infrastructure of the Internet. Data centers may also benefit from this technology through devices that could significantly increase bandwidth and speed while decreasing costs.

#### Nanotechnology

Nanotechnology refers to the development of products and production processes at the molecular level, which is a scale smaller than 100 nanometers (a nanometer is one-billionth of a meter).

#### Nitrogenous heterocyclical structure

A multi-atom molecular ring or combination of rings that contain nitrogen.

#### Plastics/Polymers

Polymers, also known as plastics, are large carbon-based molecules that bond many small molecules together to form a long chain. Polymer materials can be engineered and optimized using nanotechnology to create a system in which unique surface, electrical, chemical and electro-optic characteristics can be controlled. Materials based on polymers are used in a multitude of industrial and consumer products, from automotive parts to home appliances and furniture, as well as scientific and medical equipment.

#### Polymerization

Polymerization is a molecular engineering process that provides the environmental and thermal stability necessary for functional electro-optical devices. Polymer materials can be engineered and optimized using nanotechnology to create a system in which unique surface, electrical, chemical and electro-optic characteristics can be controlled.

Thermal Gravimetric Analysis (TGA)

The basic principle in TGA is to measure the mass of a sample as a function of temperature. This, in principle, simple measurement is an important and powerful tool in solid-state chemistry and materials science. The method, for example, can be used to determine water of crystallization, follow degradation of materials, determine reaction kinetics, study oxidation and reduction, or to teach the principles of stoichiometry, formulae and analysis.

Zwitterionic-aromatic push-pull

Most charge-transfer dyes (e.g. Disperse Red 1, CLD, FTC) have an excited state (such as during photonic absorption) wherein a full charge is separated across the molecule. Such a molecule is said to be excited-state zwitterionic. Within such a molecular system the zwitterionic state is unstable and the molecule typically collapses rapidly into its lower dipole ground state. In our patented molecular designs, the excited state is further stabilized by the aromatization of the molecular core. In that aromaticity stabilizes this excited state, it is said to "pull" the molecule into this higher energy state; on the other hand, the unstable zwitterionic state is said to "push" the molecule out of the excited state.

Our Business

Lightwave Logic, Inc. is developing a new generation of advanced organic nonlinear materials to be used to make electro-optic polymers and non-linear all-optical polymers and photonic devices that utilize them. These polymer-based materials, when used in modulators or waveguide structures, can convert high-speed electronic signals into optical (light) signals for use in communications systems, high-speed data transfer or advanced high speed computing. In the case of nonlinear all-optical polymers, certain of our Company's materials can be used in devices that use light waves to switch other light waves, in other words, have third-order properties.

Organic material with electro-optic characteristics is the core active ingredient in high-speed fiber-optic telecommunication systems. Utilizing our proprietary technology, we are in the process of engineering advanced organic polymers that we believe may lead to significant performance advancements, component size and cost reduction, ease of processing, and thermal and temporal stability. We believe that polymer materials engineered at the molecular level may have a significant role in the future development of commercially significant electro-optic related products.

Our organic materials work by affecting the optical properties of light in the presence of an electric field at extremely high frequencies (wide bandwidths), but possess inherent advantages to inorganic materials.

Currently, the core electro-optic material contained in most modulators is a crystalline material, such as lithium niobate or gallium arsenide. The following chart describes some of the characteristics of crystalline materials and electro-optical polymers.

Crystalline Materials

Electro-optical Polymers

Must be manufactured in strict dust-free conditions since even slight contamination can render them inoperable

Capable of being manufactured in less stringent environmental conditions. Capable of being tailored at the molecular level for optimal performance characteristics

More expensive to manufacture

Less expensive to manufacture

Limited to telecommunication speeds that are less than 40Gb/s (40 billion digital bits of data per second)

Demonstrated the ability to perform at speeds that are greater than 100Gb/s (100 billion digital bits of data per second)

Lithium niobate devices require large power levels (modulation voltages) to operate and are large in size -- typically measuring about four inches long (considering that most integrated circuits are literally invisible to the naked eye, these devices are enormous)

Require significantly lower power levels, up to 60% less (modulation voltages) to operate and are capable of miniaturization

Requires more elaborate, expensive mechanical packaging ( housings) generally comprised of materials, such as

Initial tests indicate no requirement for more elaborate, expensive packaging ( housings)

gold-plated Kovar, in order to assure operational integrity  
over required time and operating temperature ranges

4

---

We consider organic polymers with electro-optic qualities to be the most feasible technology for future high-speed (wide bandwidth) electronic-optical conversion. Due to the ease of processing afforded by electro-optic polymers, as well as their capacity to foster component size reduction, we believe electro-optic polymers have the potential to replace existing high-speed fiber-optics components that are used today in many commercial and military applications.

We also believe the miniaturization provided by advanced electro-optic polymers may allow for the successful fabrication of chip-to-chip (backplane) optical interconnect devices for computers that create the high-speed data transmission necessary for extremely high-speed computations. Further, we believe that additional potential applications for electro-optic polymers may include phased array radar, cable television (CATV), input-output devices for large data center applications, high speed computing, electronic counter measure (ECM) systems, ultra-fast analog-to-digital conversion, land mine detection, radio frequency photonics, spatial light modulation and all-optical (light-switching-light) signal processing.

#### Our Electro-Optic Technology Approach

Our proposed solution to produce high-performance, high-stability electro-optic polymers for high-speed (wide bandwidth) telecommunication applications lies in a less mainstream, yet firmly established, scientific phenomenon called aromaticity. Aromaticity causes a high degree of molecular stability. It is a molecular arrangement wherein atoms combine into multi-membered rings and share their electrons among each other. Aromatic compounds are stable because the electronic charge distributes evenly over a great area preventing hostile moieties, such as oxygen and free radicals, from finding an opening to attack.

For the past two decades, diverse corporate interests, including, to our knowledge, IBM, Lockheed Martin, DuPont, AT&T Bell Labs, Honeywell and 3M, as well as numerous universities and U.S. Government Agencies, have been attempting to produce high-performance, high-stability electro-optic polymers for high-speed (wide bandwidth) telecommunication applications. These efforts have largely been unsuccessful due, in our opinion, to the industry's singular adherence to an industry pervasive engineering model known as the Bond Length Alternation ("BLA") theory model. The BLA model, like all other current industry-standard molecular designs, consists of molecular designs containing long strings of atoms called polyene chains. Longer polyene chains provide higher electro-optic performance, but are also more susceptible to environmental threats, which result in unacceptably low-performing, thermally unstable electro-optic polymers.

As a result, high frequency modulators engineered with electro-optic polymers designed on the BLA model or any other polyene chain design models are unstable over typical operating temperature ranges, and often exhibit performance degradation within days, hours or even minutes. Similarly, lower frequency modulators exhibit comparable failings, but to a lesser extent. These flaws, in most cases, have prevented commercial quality polymer-based modulators operating at 10-40Gb/s from entering the commercial marketplace. The thermal stability of these devices does not generally meet the minimum Telcordia GR-468 operating temperature range (-40 degrees Celsius to +85 degrees Celsius) much less the more harsh MILSPEC 883D (military specification) range of -55 degrees Celsius to 150 degrees Celsius.

None of our patented molecular designs rely on the BLA polyene chain design model.

## Our Intellectual Property

### Issued U.S. Patents:

- US 7 919 619 - Heterocyclical Chromophore Architectures (Granted April 5, 2011)
- US 7 894 695 - Tricyclic Spacer Systems for Nonlinear Optical Devices (Granted – February 22, 2011)
- US 8 269 004 - Heterocyclical Chromophore Architectures (Granted September 18, 2012)
- US 8 298 326 - Tricyclic Spacer Systems for Nonlinear Optical Devices (Granted- October 30, 2012)

### Issued Australian Patents:

- AU 2005302506 - Heterocyclical Chromophore Architectures (Granted November 29, 2012)

### Allowed Japanese Patents:

- JP 539187/2007 - Heterocyclical Chromophore Architectures (Granted March 19, 2013)

We have twenty-six pending patent applications (including six patent families with applications in Australia, Canada, China, European Patent Office, Japan and the U.S. based on the PCT and U.S. applications below) in the field of nonlinear optic chromophore design as follows:

- 12/956597 - Stable Free Radical Chromophores, processes for preparing the same.
- 13/307663 - Stable Free Radical Chromophores, processes for preparing the same.
- PCT/US05/39212 - Tricyclic Spacer Systems for Nonlinear Optical Devices
- PCT/US05/39664 - Anti-Aromatic Chromophore Architectures
- PCT/US05/39213 - Heterocyclical Anti-Aromatic Chromophore Architectures
- PCT/US05/39010 - Heterocyclical Chromophore Architectures
- PCT/US06/11637 - Heterocyclical Chromophore Architectures with Novel Electronic Acceptor Systems.

### Heterocyclical Anti-Aromatic Systems

Two of our provisional patents cover heterocyclical anti-aromatic electronic conductive pathways, which are the heart of our high-performance, high-stability molecular designs. The completely heterocyclical nature of our molecular designs "lock" conductive atomic orbitals into a planar (flat) configuration, which provides improved electronic conduction and a significantly lower reaction to environmental threats (e.g. thermal, chemical, photochemical, etc.) than the BLA design paradigm employed by other competitive electro-optic polymers.

The anti-aromatic nature of these structures dramatically improves the "zwitterionic-aromatic push-pull" of the systems, providing for low energy charge transfer. Low energy charge transfer is important for the production of extremely high electro-optic character.

**Heterocyclical Steric Hindering System** This patent describes a nitrogenous heterocyclical structure for the integration of steric hindering groups that are necessary for the nanoscale material integration. Due to the [pi]-orbital configuration of the nitrogen bridge, this structure has been demonstrated not to interfere with the conductive nature of the electronic conductive pathway and thus is non-disruptive to the electro-optic character of the core molecular construction. The quantum mechanical design of the system is designed to establish complete molecular planarity (flatness) for optimal performance.



**Totally Integrated Material Engineering System** This patent covers material integration structures under a design strategy known as Totally Integrated Material Engineering. These integration structures provide for the "wrapping" of the core molecule in sterically hindering groups that maximally protect the molecule from environmental threats and maximally protect it from microscopic aggregation (which is a major cause of performance degradation and optical loss) within a minimal molecular volume. These structures also provide for the integration of polymerizable groups for integration of materials into a highly stable cross-linked material matrix.

#### Historic Breakthroughs and Results

During 2004, independent quantum mechanical calculations performed on our electro-optic polymer designs at government laboratories located at the Naval Air Warfare Center Weapons Division in China Lake, California suggested that our initial aromatic molecules perform two and a half (2.5) to three and three-tenths (3.3) times more efficiently than currently available telecom grade electro-optic polymers. Our conclusion was that performance improvements of this magnitude indicate a significant breakthrough in the field of fiber-optic telecommunication.

In May and June of 2006, performance evaluations of one of our first extremely high-performance electro-optic materials were performed by electro-optic expert, Dr. C.C. Teng, co-inventor of the renowned Teng-Man test, and subsequently confirmed by the University of Arizona's College of Optical Sciences. Under identical laboratory conditions at low molecular loadings, one of our molecular designs outperformed one of the industry's highest performance electro-optic systems by a factor as high as 650%. Our conclusion was that the Teng-Man test established the validity of our novel, patent pending molecular design paradigm known as CSC (Cyclical Surface Conduction) theory; and that the success of CSC theory has the potential to establish the fundamental blueprint of electro-optic material design for decades to come, and to have broad application in commercial and military telecommunication and advanced computational systems.

On September 25, 2006 we obtained independent laboratory results that confirmed the thermal stability of our Perkinamine™ electro-optic materials. Thermal stability as high as 350 degrees Celsius was confirmed, significantly exceeding many other then commercially available high performance electro-optic materials, such as CLD-1 that exhibits thermal degradation in the range of 250 degrees Celsius to 275 degrees Celsius. This high temperature stability of our materials eliminates a major obstacle to vertical integration of electro-optic polymers into standard microelectronic manufacturing processes (e.g. wave/vapor-phase soldering) where thermal stability of at least 300 degrees Celsius is required. In independent laboratory tests, ten-percent material degradation, a common evaluation of overall thermal stability, did not occur until our Perkinamine™ materials base was exposed to temperatures as high as 350 degrees Celsius, as determined by Thermo-Gravimetric Analysis (TGA). The test results supported our Company's progress to introduce our materials into commercial applications such as optical interconnections, high-speed telecom and datacom modulators, and military/aerospace components.

On September 26, 2006, we were awarded the 2006 Electro-Optic Materials Technology Innovation of the Year Award by Frost & Sullivan. Frost & Sullivan's Technology Innovation of the Year Award is bestowed upon candidates whose original research has resulted in innovations that have, or are expected to bring, significant contributions to multiple industries in terms of adoption, change, and competitive posture. This award recognizes the quality and depth of our Company's research and development program as well as the vision and risk-taking that enabled us to undertake such an endeavor.

In July 2007, our Company developed an innovative process to integrate our unique architecture into our anticipated commercial devices, whereby dendritic spacer systems are attached to its core chromophore. In the event we are successful in developing a commercially viable product, we believe these dendrimers will reduce the cost of manufacturing materials and reduce the cost and complexity of tailoring the material to specific customer requirements.



In March 2008, we commenced production of our first prototype photonic chip, which we delivered to Photon-X, LLC to fabricate a prototype polymer optical modulator and measure its technical properties. In June 2009 we released